



UNISOUND UNDERLAY


Technical data sheet
English


QUICK-STEP
FLOOR DESIGNERS

General information

Great all-round underlay for rooms with frequent traffic, such as your living room, hallway and kitchen.

The Unisound underlay has a closed cell structure which gives it the ability to return to its original state after being compressed, even after using it for years. It has an integrated vapour barrier and a lip and tape strip for easy installation.



Unisound Underlay

| | |
|----------------------|--------------------------|
| Order code | QSUDLDRUCO15 |
| M² | 15 m ² |
| Dimensions | 15960 x 940 x 2 mm |
| Weight | 3.269 kg |
| Composition | Crosslinked polyethylene |

Unisound Underlay

Colour

White

Applicable for:

The use of accessories other than those supplied by Quick-Step may cause damage to the Quick-Step floor. In such case the guarantee provided by Quick-Step will be void. We therefore strongly recommend to use only Quick-Step accessories as these have been especially designed and tested for use with Quick-Step floor panels.

Features

Installing the correct underlay has a major impact on the look, quality, acoustics and longevity of your finished floor.

✓ **Creates a level base**

A good underlay provides the stable foundation that your quality floor deserves.

✓ **Supports your click system**

Suitable for installation under Laminate and Parquet floors.

✓ **Acoustic insulation**



The underlay provides very good sound reduction in the room and very good sound reduction to the rooms below.

✓ **Thermal resistance**

Compatible with Laminate floors in combination with underfloor heating (not Parquet on underfloor heating systems). Not compatible with underfloor cooling systems. Please follow carefully our underfloor heating instructions to avoid any damage.

✓ **Quick-Step warranty**

Underlays come with the same warranty as your floor.



Performance

If you're going for a quick and smooth floating installation, choosing the right underlay is essential. All performance tests are carried out in accordance with EN-16354.

Summary

| | |
|--------------------------------|--------------------------|
| Punctual conformability | 1,4 mm |
| Compressive strength | 70 kPa |
| Compressive creep | 17 kPa |
| Dynamic load | > 100.000 |
| Moisture resistance | 75 m |
| Impact sound | 19 dB |
| Reflected walking sound | ★★★★☆ |
| Thermal resistance | 0,049 m ² K/W |

Moisture resistance

| | |
|--------------------|---|
| Description | Protection against rising damp. |
| Result | 75 m |
| Test method | EN-16354 |
| Importance | It is advised to install an underlay with integrated vapor barrier in order to protect your floor from rising damp. To be fully moisture resistant, all seams must be sealed with a moisture proof tape. Quick-Step Unisound underlay has an integrated vapour barrier, so there's no need to install a separate damp foil. A lip and tape strip are also attached to the underlay to ensure fast installation. |

Impact sound

| | |
|--------------------|---|
| Description | The sound waves that travel through your floor and can be an annoyance to your neighbours. |
| Result | 19 dB |
| Test method | Impact sound reduction is expressed as ΔL_w and gives the weighted reduction of impact sound pressure and is measured according to the EN-16354 protocol. |
| Importance | Impact sound can be a cause of annoyance and friction between neighbours. Check your local Building Codes / Standards for any specific requirements. |

Reflected walking sound

Description

The sound you hear when you walk across the floor.

Result

★★★★☆

Test method

The reflected walking sound is measured according to EN-16205. There is no general rating scale, therefore we rate the impact of the various underlays on reflective walking sound in stars at Quick-Step.

Importance

In rooms with lots of traffic, the tapping noise of shoes can be experienced as very annoying. Thanks to its closed cell structure, the Unisound underlay always returns to its original state. Therefore the underlay fits closely onto the floor and it reduces reflected walking sound to a minimum.

Thermal resistance

Description

This underlay is suitable for underfloor heating in combination with Laminate floors, not in combination with Parquet floors. It's not compatible with underfloor cooling.

Result

0,049 m²K/W

Test method


EN-16354

Importance

The thermal resistance of an underlay measures the temperature difference when there is a thermal transfer through the material. It is the thickness of the product divided by its conductivity and its measuring unit is m²K/W. This value needs to be either high or low depending on the preference of the customer. For application over underfloor heating, this value needs to be low and for situations where additional insulation is required, this value needs to be high. When evaluating the thermal resistance, the thermal resistance of the entire flooring system (floor + underlay) needs to be added up. For applications on top of underfloor heating systems, this value cannot exceed 0,15m²K/W, for underfloor cooling this cannot exceed 0,10m²K/W. Please follow carefully our underfloor heating instructions. Should you have any further questions or problems, please do not hesitate to contact our technical department via technical.services@unilin.com.

Installation

Before installing your Quick-Step flooring, you must install an underlay. A good underlay provides the stable foundation that your quality floor deserves.



1. Unroll the underlay on the subfloor with the logo upwards. The subfloor must be clean, dry and flat. Lay the underlay strips parallel to the laying direction of your floor.
2. Lay the first underlay row and lay the next row with flap next to the first. Remove the adhesive strip from the first row and stick the foil flap of the second row on top of the adhesive. Do this strip by strip, as the laying of your floor progresses. Make sure the underlay fits together tightly and don't leave any gaps.
3. Seal the joints on the short side between two underlays with our damp-proof tape (NETAPE50), except for wooden subfloors.